

### FAG NJ2216-E-TVP2参数

尺寸	d	80	mm	-
	D	140	mm	-
	B	33	mm	-
	B <sub>1</sub>	8	mm	-
	B <sub>2</sub>	12.5	mm	-
	D <sub>1</sub>	122.9	mm	-
	D <sub>a max</sub>	129	mm	-
	d <sub>1</sub>	101.5	mm	-
	d <sub>a max</sub>	94	mm	-
	d <sub>a min</sub>	91	mm	-
	d <sub>c min</sub>	104	mm	-
	F	95.3	mm	-
	r <sub>1 min</sub>	2	mm	-
	r <sub>a max</sub>	2	mm	-
	r <sub>a1 max</sub>	2	mm	-
	r <sub>min</sub>	2	mm	-
	s	1.3	mm	距离中心位置的轴向偏移
重量	m	2040	g	质量
基本额定载荷	C <sub>r</sub>	221000	N	基本额定动载荷，径向
	C <sub>0r</sub>	244000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	6100	r/min	极限转速
参考转速	n <sub>B</sub>	3450	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	43500	N	疲劳极限载荷，径向

### FAG NJ2216-E-TVP2图片





参考资料:<http://www.sozhou.com/p/d318ef7b.html>